



Mulu

Mulu Standard IP65 LED emergency exit sign bulkhead, Black

Kosnic's LED Emergency Exit Sign or Emergency Bulkhead Luminaire is a self-contained, multi-purpose, nonmaintained or maintained* 3-hour emergency exit sign or emergency luminaire solution. The fitting can be used with or without the emergency exit graphics. It is supplied with adaptable self-adhesive graphics that can be arranged to indicate escape routes as necessary.

EESN0105S65-BLK ()

Specification

Voltage	220-240 Vac 50-60 Hz
Current (mA)	46
Rated Power (W)	5
CCT Words	Day Light
CCT (K)	6500
Total Luminous Flux (lm)	190 (white, no graphics), 150 (black, no graphics), 70 (white, with graphics), 40 (black, with graphics)
Beam Angle(°)	120
Nominal Lifetime (h)	40000
Power Factor	0.47
Ambient Temperature Range (°C)	-10 to 40
Protection Rating	Class II
IP Rating	IP65
Battery Capacity	2000 mAh
Battery Charging Time	12 hours
Battery Code	KBAT2000LI1
Battery Life	4 years
Battery Type	Li-Ion
Battery Voltage	3.6V
Battery Warranty	4 Years
Emergency Operation Test	Manual
Emergency Conversion Time	1 second
Emergency Operating Time	3 hours

Light Source Specification

Lumen Maintenance Factor (x.xx)	0.75
---------------------------------	------

Optional Gears and Accessories

Accessories 1	BAT15NC3
---------------	----------

Technical Drawings

