



Mulu

Mulu Self-Test IP65 LED emergency exit sign bulkhead

Kosnic's LED Emergency Exit Sign or Emergency Bulkhead Luminaire is a self-contained, multi-purpose, nonmaintained or maintained* 3-hour emergency exit sign or emergency luminaire solution. The fitting can be used with or without the emergency exit graphics. It is supplied with adaptable self-adhesive graphics that can be arranged to indicate escape routes as necessary.

EESN0105S65/S ()

Specification

Voltage	220-240 Vac 50-60 Hz
Current (mA)	46
Rated Power (W)	5
CCT Words	Day Light
CCT (K)	6500
Total Luminous Flux (lm)	360 (maintained, no graphics), 130 (emergency, no graphics), 200 (maintained, with graphics), 70 (emergency, with graphics)
Beam Angle(°)	120
Nominal Lifetime (h)	30000
Power Factor	0.47
Ambient Temperature Range (°C)	0 to 40
Protection Rating	Class II
IP Rating	IP65
Battery Capacity	2600 mAh
Battery Charging Time	24 hours
Battery Code	KBAT2600LI1
Battery Life	4 years
Battery Type	Li-Ion
Battery Voltage	3.6V
Battery Warranty	4 Years
Emergency Operation Test	Self-Test (ATS Type S)
Emergency Conversion Time	1 second
Emergency Operating Time	3 hours

Light Source Specification

Lumen Maintenance Factor (x.xx)	0.75
---------------------------------	------

Optional Gears and Accessories

Accessories 1	Li-ion Battery KBAT2600LI1
---------------	----------------------------

Technical Drawings

