



G9, G4, GY6.35

14W Halogen G4 Lamp

For domestic and professional environments where perfect colour reproduction and minimal UV emission is essential, Kosnic offers halogen capsules. Lamps give a crisp light with outstanding colour reproduction.

HAL14CPL/G4 ()

Specification

Voltage	12V
Current (mA)	1192
Rated Power (W)	14
CCT Words	Warm White
CCT (K)	2800
Total Luminous Flux (lm)	225
L70B50 Lifetime (h)	3000
Blue Light Hazard	RG1
Power Factor	1
Ambient Temperature Range (°C)	-20 to 40
Weight (kg)	0.008

Light Source Specification

Lighting Technology Used	HL
Directional / Non Directional (DLS/NDLS)	NDLS
Light Source Cap Type (or other interface)	G4
Mains / Non-Mains (MLS/NMLS)	NMLS
Connected Light source (Y/N)	N
Colour Tunable Light Source (Y/N)	N
High Luminance Light Source (Y/N)	N
Anti-Glare Shield (Y/N)	N
Dimmable (Y/N/Specific dimmer)	Y
Energy Consumption in on-mode (kWh/1000H)	14
Energy Efficiency Class	G
Useful Luminous Flux (lm)	225
Beam Angle correspondence (in 360°/120°/90°)	in 360°
CCT	2800
On-Mode Power (Pon) (W)	14.3
Standby Power (Psb) (W)	0

Networked Standby Power (Pnet) (W)	N/A
CRI	100
CRI (min)	100
CRI (max)	100
Height (mm)	33
Width (mm)	9
Depth (mm)	9
Claim of Equivalent Power? (Y/N)	Y
Equivalent Power (W)	26
Chromaticity Co-Ordinates (X)	0.444
Chromaticity Co-Ordinates (Y)	0.410

Technical Drawings

