



Indus

Indus 5ft Single non-corrosive linear luminaire for Kosnic LED T8 lamps with built-in emergency

The Kosnic Indus IP65 Battens for T8 LED Tubes are designed specifically for use with Kosnic's T8 LED Tubes. The luminaires are suitable for a wide range of indoor and outdoor commercial applications including warehouses, factories and garages, and have the option to include built-in emergency modules. The Kosnic T8 LED Tubes themselves utilise high performance LEDs to offer outstanding lumen efficiency with a long operational life helping to reduce building energy and maintenance costs.

KBTNT8LS655F1/E (04155)

Specification

Voltage	220-240Vac 50/60Hz
---------	--------------------

Rated Power (W)	50
-----------------	----

Ambient Temperature Range (°C)	-20 to 40
--------------------------------	-----------

Protection Rating	Class I
-------------------	---------

IK Rating	IK08
-----------	------

IP Rating	IP65
-----------	------

Emergency Luminous Flux (lm)	300 with CEW05LBL/N
------------------------------	---------------------

Light Source Specification

Light Source Cap Type (or other interface)	Terminals
--	-----------

Optional Gears and Accessories

Optional Gears 1	for 1 x 5ft LED T8 Lamp
------------------	-------------------------

Optional Gears 2	Lamp Holder G 13
------------------	------------------

Optional Gears 3	LOR (%) 92
------------------	------------

Optional Gears 4	Mounting Spacing LF (mm) 1000
------------------	-------------------------------

Optional Gears 5	CEW05LBL/N
------------------	------------

Optional Gears 6	KBAT2600
------------------	----------

Technical Drawings

