



Indus

Indus 5ft Twin non-corrosive linear luminaire for Kosnic LED T8 lamps with built-in emergency

The Kosnic Indus IP65 Battens for T8 LED Tubes are designed specifically for use with Kosnic's T8 LED Tubes. The luminaires are suitable for a wide range of indoor and outdoor commercial applications including warehouses, factories and garages, and have the option to include built-in emergency modules. The Kosnic T8 LED Tubes themselves utilise high performance LEDs to offer outstanding lumen efficiency with a long operational life helping to reduce building energy and maintenance costs.

KBTNT8LS655F2/E (06390)

Specification

Voltage	220-240Vac 50/60Hz
Rated Power (W)	2 x 50
Ambient Temperature Range (°C)	-20 to 40
Protection Rating	Class I
IK Rating	IK08
IP Rating	IP65
Emergency Luminous Flux (lm)	300 with CEW05LBL/N

Light Source Specification

Light Source Cap Type (or other interface)	Terminals
--	-----------

Optional Gears and Accessories

Optional Gears 1	for 2 x 5ft LED T8 Lamp
Optional Gears 2	Lamp Holder G 13
Optional Gears 3	LOR (%) 92
Optional Gears 4	Mounting Spacing LF (mm) 1000
Optional Gears 5	CEW05LBL/N
Optional Gears 6	KBAT2600

Technical Drawings

