



## Indus

### Indus 6ft Single non-corrosive linear luminaire for Kosnic LED T8 lamps with built-in emergency

The Kosnic Indus IP65 Battens for T8 LED Tubes are designed specifically for use with Kosnic's T8 LED Tubes. The luminaires are suitable for a wide range of indoor and outdoor commercial applications including warehouses, factories and garages, and have the option to include built-in emergency modules. The Kosnic T8 LED Tubes themselves utilise high performance LEDs to offer outstanding lumen efficiency with a long operational life helping to reduce building energy and maintenance costs.

**KBTNT8LS656F1/E** (04434)

### Specification

|         |                    |
|---------|--------------------|
| Voltage | 220-240Vac 50/60Hz |
|---------|--------------------|

|                 |    |
|-----------------|----|
| Rated Power (W) | 50 |
|-----------------|----|

|                                |           |
|--------------------------------|-----------|
| Ambient Temperature Range (°C) | -20 to 40 |
|--------------------------------|-----------|

|                   |         |
|-------------------|---------|
| Protection Rating | Class I |
|-------------------|---------|

|           |      |
|-----------|------|
| IK Rating | IK08 |
|-----------|------|

|           |      |
|-----------|------|
| IP Rating | IP65 |
|-----------|------|

|                              |                     |
|------------------------------|---------------------|
| Emergency Luminous Flux (lm) | 300 with CEW05LBL/N |
|------------------------------|---------------------|

### Light Source Specification

|                                            |           |
|--------------------------------------------|-----------|
| Light Source Cap Type (or other interface) | Terminals |
|--------------------------------------------|-----------|

### Optional Gears and Accessories

|                  |                         |
|------------------|-------------------------|
| Optional Gears 1 | for 1 x 6ft LED T8 Lamp |
|------------------|-------------------------|

|                  |                  |
|------------------|------------------|
| Optional Gears 2 | Lamp Holder G 13 |
|------------------|------------------|

|                  |            |
|------------------|------------|
| Optional Gears 3 | LOR (%) 90 |
|------------------|------------|

|                  |                               |
|------------------|-------------------------------|
| Optional Gears 4 | Mounting Spacing LF (mm) 1325 |
|------------------|-------------------------------|

|                  |            |
|------------------|------------|
| Optional Gears 5 | CEW05LBL/N |
|------------------|------------|

|                  |          |
|------------------|----------|
| Optional Gears 6 | KBAT2600 |
|------------------|----------|

## Technical Drawings

