



Havasu

Havasu Floodlight, LED Type IV

The Kosnic Havasu LED floodlights are high-power premium luminaires available in two sizes, both with wattage switching, and can be supplied with a variety of illumination pattern choices. The floodlights are IP66 rated for outdoor use, robust and have high lumen efficiency and a long life.

KFLD200-240Q666-A150 ()

Specification

Voltage	100-277Vac 50/60Hz
Current (mA)	887/1065
Rated Power (W)	200/240
CCT Words	Day Light
CCT (K)	5000
Total Luminous Flux (lm)	30000/36000
Beam Angle(°)	Spot (70° x 30°), Flood (60° x 60°), Wide (90° x 90°), Type IV (140° x 50°), Asymmetric 50 (120° x 50°)
Nominal Lifetime (h)	54000
SDCM of CCT	<6
Flicker %	1
Power Factor	0.98
Dimensions (L x W x D) (mm)	495 x 427 x 70 (vertical mounting surface to face 180)
Ambient Temperature Range (°C)	-30 to 45
Weight (kg)	6.2
In-rush current (peak/duration) (A)	85 / 500 us
Protection Rating	Class I
IK Rating	IK08
IP Rating	IP66

Light Source Specification

Dimmable (Y/N/Specific dimmer)	N
CRI	>70
Lumen Maintenance Factor (x.xx)	0.9

Optional Gears and Accessories

Optional Gears 1	Connection - supplied with 1m of H05RN-F 3 x 1.0mm ² to internal terminals
------------------	---

Technical Drawings

