



DD, T5C CFL Lamp

21W Plug-in fluorescent DD lamp

A comprehensive range of plug-in compact fluorescent DD lamps with premium specifications. Designed for use in a wide variety of commercial and industrial applications such as offices, warehouses and supermarkets, these lamps deliver a high lumen to wattage ratio and are extremely robust and durable.

KFT21STD/4P-835 ()

Specification

Voltage	Nominal Voltage 230V
Rated Power (W)	21
CCT Words	Soft White
CCT (K)	3500
Total Luminous Flux (lm)	1350
L70B50 Lifetime (h)	12000

Light Source Specification

Lighting Technology used	CFL
Directional / Non Directional (DLS/NDLS)	NDLS
Light Source Cap Type (or other interface)	GR10q (4 pin)
Mains / Non-Mains (MLS/NMLS)	NMLS
Connected Light source (Y/N)	N
Colour Tunable Light Source (Y/N)	N
High Luminance Light Source (Y/N)	N
Anti-Glare Shield (Y/N)	N
Dimmable (Y/N/Specific dimmer)	N
Energy Consumption in on-mode (kWh/1000H)	21
Energy Efficiency Class	A (Previous formula)
Useful Luminous Flux (lm)	1350
CCT	3500K
On-Mode Power (Pon) (W)	21
CRI	>80
Height (mm)	140
Width (mm)	138
Survival Factor (x.xx)	LSF at 2000h 0.99
Lumen Maintenance Factor (x.xx)	LLMF at 2000h 0.85

Optional Gears and Accessories

Optional Gears 1

Operation Mode for Ratings 50Hz

Technical Drawings

