



DD, T5C CFL Lamp

28W Plug-in fluorescent DD lamp

A comprehensive range of plug-in compact fluorescent DD lamps with premium specifications. Designed for use in a wide variety of commercial and industrial applications such as offices, warehouses and supermarkets, these lamps deliver a high lumen to wattage ratio and are extremely robust and durable.

KFT28STD/4P-840 ()

Specification

Voltage	Nominal Voltage 230 V
Rated Power (W)	28
CCT Words	Cool White
CCT (K)	4000
Total Luminous Flux (lm)	2050
L70B50 Lifetime (h)	12000

Light Source Specification

Lighting Technology Used	CFL
Directional / Non Directional (DLS/NDLS)	NDLS
Light Source Cap Type (or other interface)	GR10q (4 pin)
Mains / Non-Mains (MLS/NMLS)	NMLS
Connected Light source (Y/N)	N
Colour Tunable Light Source (Y/N)	N
High Luminance Light Source (Y/N)	N
Anti-Glare Shield (Y/N)	N
Dimmable (Y/N/Specific dimmer)	N
Energy Consumption in on-mode (kWh/1000H)	28
Energy Efficiency Class	A (Previous formula)
Useful Luminous Flux (lm)	2050
CCT	4000K
On-Mode Power (Pon) (W)	28
CRI	>80
Height (mm)	200
Width (mm)	198
Survival Factor (x.xx)	LSF at 2000h 0.99
Lumen Maintenance Factor (x.xx)	LLMF at 2000h 0.85

Optional Gears and Accessories

Optional Gears 1

Operation Mode for Ratings 50Hz

Technical Drawings

