



Petal

High Bay Petal Lamp, 30W, E27, 5000K

The Kosnic Petal lamps offer energy savings and high performance, replacing conventional high-level lighting in industrial areas, manufacturing, warehousing, leisure facilities and retail environments. The lamps are self-ballasted and run directly from the mains supply, so no ballast is required.

KHBL30PTL/E27-W50 ()

Specification

Voltage	220-240Vac 50-60Hz
Current (mA)	133, 140
Rated Power (W)	30
CCT Words	Day Light
CCT (K)	5000K
Beam Angle(°)	180, 330
Nominal Lifetime (h)	20000, 25000
SDCM (McAdam Ellipses) for CCT	1.7
Power Factor	0.93, 0.98
Weight (kg)	0.27, 0.37
Switch Cycles	15000
Warm-up Time 60% Φ (X.X S)	0.5
Warm-up Time 95% Φ (X.X S)	0.6
6) LED lamp requiring external power supply	No
Lamp Cap	E27
LM at 6000h	0.85
LM at Nominal Lifetime	0.8
Mercury (X.X mg)	0
Prem Fail Rate at 1000h (%)	5
Rated Luminous Flux (Φ)	3000, 3300
Start Time (X.X S)	0.5

Light Source Specification

CRI	84
-----	----

Technical Drawings

