



## Petal

### High Bay Petal Lamp, 50W, E40, 2200K

The Kosnic Petal lamps offer energy savings and high performance, replacing conventional high-level lighting in industrial areas, manufacturing, warehousing, leisure facilities and retail environments. The lamps are self-ballasted and run directly from the mains supply, so no ballast is required.

**KHBL50PTL/E40-W22 ()**

## Specification

|                                             |                    |
|---------------------------------------------|--------------------|
| Voltage                                     | 220-240Vac 50-60Hz |
| Current (mA)                                | 222                |
| Rated Power (W)                             | 50                 |
| CCT Words                                   | Warm White         |
| CCT (K)                                     | 2200K              |
| Beam Angle(°)                               | 330                |
| Nominal Lifetime (h)                        | 20000              |
| Power Factor                                | 0.98               |
| Weight (kg)                                 | 0.379              |
| Switch Cycles                               | 15000              |
| Warm-up Time 60% $\Phi$ (X.X S)             | 0.5                |
| Warm-up Time 95% $\Phi$ (X.X S)             | 0.6                |
| 6) LED lamp requiring external power supply | No                 |
| Lamp Cap                                    | E40                |
| LM at 6000h                                 | 0.85               |
| LM at Nominal Lifetime                      | 0.8                |
| Mercury (X.X mg)                            | 0                  |
| Prem Fail Rate at 1000h (%)                 | 5                  |
| Rated Luminous Flux ( $\Phi$ )              | 5200               |
| Start Time (X.X S)                          | 0.5                |

## Light Source Specification

|     |     |
|-----|-----|
| CRI | >80 |
|-----|-----|

## Technical Drawings

