



DD Standard I

DD Standard I 18W Retrofit replacement for popular CFL DD lamps, 4pin, 30000hrs, 2700K

Kosnic's range of LED DD lamps takes a fresh approach to functional lighting with a design philosophy offering plug-in emergency packs and optional microwave sensor versions so that there are no barriers to retrofitting LEDs in commercial fittings. The products bring the energy saving capabilities of LED technology to the commercial environment and the lamps can quickly replace fluorescent DD lamps with little or no rewiring.

KLED18STD/4P-W27 ()

Specification

Voltage	220-240Vac 50-60Hz
Current (mA)	87
Rated Power (W)	18
CCT Words	Warm White
CCT (K)	2700K
Beam Angle(°)	114
Nominal Lifetime (h)	30000
SDCM (McAdam Ellipses) for CCT	2.6
Power Factor	0.9
Switch Cycles	50000
Warm-up Time 60% Φ (X.X S)	0.5
Warm-up Time 95% Φ (X.X S)	0.6
6) LED lamp requiring external power supply	No
Lamp Cap	GR10q
LM at 6000h	0.85
LM at Nominal Lifetime	0.75
Mercury (X.X mg)	0
Prem Fail Rate at 1000h (%)	1
Rated Peak Candela (cd)	590
Rated Luminous Flux (Φ)	1780
Start Time (X.X S)	0.39

Light Source Specification

CRI	83
-----	----

Technical Drawings

