



Kali Pro

Kali Pro LED Panel 23W/28W Switchable Wattage, 6500K

• Switchable wattage (23W default/28W) • Save up to 50% energy usage compared to traditional fluorescent fittings • UGR <19 according to BS EN 12464 • TP(a) rated diffuser • Supplied with flicker-free DC driver as standard • Compatible with the Kosnic emergency modules • DALI, 1-10V and PUSH dimmable alternative drivers available • Optional surface and suspension mounting kits available • IP44 when ceiling recess mounted • Long life of 40,000h • Slim profile designs • Instant start

KLED2328PNL-W65 ()

Specification

Voltage	220-240Vac 50-60Hz
Current (mA)	111, 132
Rated Power (W)	23, 28
CCT Words	Day Light
CCT (K)	6500K
Nominal Lifetime (h)	40000
SDCM (McAdam Ellipses) for CCT	<6
Power Factor	0.9
Weight (kg)	1.84
Switch Cycles	50000
Warm-up Time 60% Φ (X.X S)	0.5
Warm-up Time 95% Φ (X.X S)	0.6
6) LED lamp requiring external power supply	No
Lamp Cap	N/A
LM at 6000h	0.85
LM at Nominal Lifetime	0.75
Prem Fail Rate at 1000h (%)	1
Rated Luminous Flux (Φ)	3000, 3400
Start Time (X.X S)	0.15

Light Source Specification

CRI	≥ 80
-----	-----------

Technical Drawings

