



Kali Pro

Kali Pro LED Panel 36W/27W Switchable Wattage, 4000K

• Switchable wattage (27W/36W default) • Save up to 50% energy usage compared to traditional fluorescent fittings • Can achieve UGR<17* • TP(a) rated diffuser • Supplied with flicker-free DC driver as standard • Dimmable DALI/1-10V/PUSH driver available • Compatible with the Kosnic emergency modules • Optional surface and suspension mounting kits available • IP44 when ceiling recess mounted • Long life of 40,000h • Slim profile designs • Instant start

KLED3627PNL-W40 ()

Specification

Voltage	220-240Vac 50-60Hz
Current (mA)	126, 165
Rated Power (W)	27, 36
CCT Words	Cool White
CCT (K)	4000K
Nominal Lifetime (h)	40000
SDCM (McAdam Ellipses) for CCT	<6
Power Factor	0.93, 0.95
Weight (kg)	2.26
Switch Cycles	50000
Warm-up Time 60% Φ (X.X S)	0.5
Warm-up Time 95% Φ (X.X S)	0.6
6) LED lamp requiring external power supply	No
Lamp Cap	N/A
LM at 6000h	0.85
LM at Nominal Lifetime	0.75
Prem Fail Rate at 1000h (%)	1
Rated Luminous Flux (Φ)	3100, 4000
Start Time (X.X S)	0.15

Light Source Specification

CRI	≥ 80
-----	-----------

Technical Drawings

