



Codale

Codale 35W Surface or pendant LED circular panel

Kosnic's LED Circular Surface or Pendant Luminaire offers a low maintenance solution to lighting for all areas, including visually demanding non-transient task areas such as offices and educational premises where users require uniform light to maintain well-being. Choose the luminaire that is required and then select the back-box containing the driving components. The back-box output will adjust to suit the luminaire. The back-boxes are available as standard, emergency, sensor or sensor and emergency. The back-box can be surface mounted or suspended if the additional suspension kit is ordered. However, the emergency module green LED charging indicator is on the side of the back-box at the rear of the luminaire and may be difficult to see when suspended.

KPNLLS35CS-W40 ()

Specification

Voltage	42 Vdc
Current (mA)	710
Rated Power (W)	29
CCT Words	Cool White
CCT (K)	4000
Total Luminous Flux (lm)	2940
Nominal Lifetime (h)	40000
SDCM of CCT	<6
Ambient Temperature Range (°C)	-20 to 40
Protection Rating	Class III
Emergency Luminous Flux (lm)	400

Light Source Specification

Dimmable (Y/N/Specific dimmer)	N
CRI	82
Peak Luminous Intensity (DLS) (cd)	970
Lumen Maintenance Factor (x.xx)	0.75

Technical Drawings

