



Pro

6w Retrofit LED G5.3

Suitable for the most demanding of professional users, Kosnic's KPRO range offers lamps that deliver huge energy savings over halogen lamps without compromising on brightness. The lamps can quickly replace halogen products in accent and general lighting applications, and once in place rapid payback is achieved.

KPRO06PWR/G5.3-S30 ()

Specification

Voltage	12Vac/dc
Current (mA)	500
Rated Power (W)	6
CCT Words	Warm White
CCT (K)	3000K
Total Luminous Flux	330
Beam Angle(°)	45
Nominal Lifetime (h)	30000
SDCM (McAdam Ellipses) for CCT	4.6
Power Factor	1
Switch Cycles	50000
Warm-up Time 60% Φ (X.X S)	0.5
Warm-up Time 95% Φ (X.X S)	0.6
2) External LED control gear	Yes
Correction Factor	1.1
Lamp Cap	G5.3
LM at 6000h	0.85
LM at Nominal Lifetime	0.75
Mercury (X.X mg)	0
Prem Fail Rate at 1000h (%)	1
Rated Peak Candela (cd)	370
Rated Useful Luminous Flux (Φ_{use})	250
Start Time (X.X S)	0.1

Light Source Specification

CRI	82
-----	----

Technical Drawings

