



Maly

Maly Modular system of LED retail downlights, 24w 15° 5000K

The Kosnic LED Retail Downlight range offers energy efficient LED lighting with a wide variety of housing options to provide different lighting effects in a wide variety of situations. Simply choose the LED module based on the output, beam angle and colour temperature, then choose a housing option from the choices of fixed and adjustable downlighters, wall washers and twin grid spotlights. The LED module and housing clip together and are easy to fit in shops, hotels, galleries, showrooms and similar premises where a high quality, high efficiency lighting solution is required.

KRDL606M24-B50 ()

Specification

Voltage	220-240Vac 50-60Hz
Current (mA)	110
Rated Power (W)	24
CCT Words	Day Light
CCT (K)	5000
Total Luminous Flux (lm)	2000
Beam Angle(°)	15
Nominal Lifetime (h)	40000
SDCM of CCT	<6
Power Factor	0.95
Ambient Temperature Range (°C)	-20 to 40
Protection Rating	Class III Luminaire, Class II driver
IP Rating	IP20
Emergency Luminous Flux (lm)	400 (with CEW03LIC/N or CEW03LIC/S)
Driver Part Number	CYC026SNL058N
Driver Input Voltage	180-264Vac 50-60Hz
Driver Maximum Input Current (mA)	135
Driver Maximum Power (W)	26
Driver Output Voltage (Vdc)	26~46Vdc
Driver Output Current (mA)	580
Driver Dimensions (L x W x D) (mm)	154 x 47 x 34
Driver Power Factor	0.96
Driver Ripple Current (%)	<10%
Driver Maximum Case Temperature (°C)	75

Light Source Specification

Lighting Technology Used	LED
Directional / Non Directional (DLS/NDLS)	DLS
Light Source Cap Type (or other interface)	Connection - driver wiring leads

Mains / Non-Mains (MLS/NMLS)	NMLS
Dimmable (Y/N/Specific dimmer)	No
CCT	5000K
CRI	82
Lumen Maintenance Factor (x.xx)	0.75

Technical Drawings

