



Maly

Maly Modular system of LED retail downlights, 34w 40° 5000K

The Kosnic LED Retail Downlight range offers energy efficient LED lighting with a wide variety of housing options to provide different lighting effects in a wide variety of situations. Simply choose the LED module based on the output, beam angle and colour temperature, then choose a housing option from the choices of fixed and adjustable downlighters, wall washers and twin grid spotlights. The LED module and housing clip together and are easy to fit in shops, hotels, galleries, showrooms and similar premises where a high quality, high efficiency lighting solution is required.

KRDL607M34-S50 ()

Specification

Voltage	220-240Vac 50-60Hz
Current (mA)	137
Rated Power (W)	34
CCT Words	Day Light
CCT (K)	5000
Total Luminous Flux (lm)	3200
Beam Angle(°)	40
Nominal Lifetime (h)	40000
SDCM of CCT	<6
Power Factor	0.95
Protection Rating	Class III Luminaire, Class II driver
IP Rating	IP20
Emergency Luminous Flux (lm)	300 (with CEW03LIC/N or CEW03LIC/S)
Driver Part Number	CYC036SNL080N
Driver Input Voltage	220-240Vac 50/60Hz
Driver Maximum Input Current (mA)	150
Driver Maximum Power (W)	29.4
Driver Output Voltage (Vdc)	30-42 Vdc
Driver Output Current (mA)	700
Driver Dimensions (L x W x D) (mm)	97 x 43 x 30
Driver Power Factor	≥0.95
Driver Ripple Current (%)	<5%
Driver Maximum Case Temperature (°C)	70

Light Source Specification

Lighting Technology Used	LED
Directional / Non Directional (DLS/NDLS)	DLS
Light Source Cap Type (or other interface)	Connection - driver wiring leads
Mains / Non-Mains (MLS/NMLS)	NMLS

Dimmable (Y/N/Specific dimmer)	No
CCT	5000K
CRI	82
Lumen Maintenance Factor (x.xx)	0.75

Technical Drawings

