



PAR30

10w Retro-fit replacement of halogen PAR spotlight

An LED reflector lamp that provides maximum energy savings, which is a replacement for common halogen PAR30 lamps. Suitable for accent and general lighting applications in hospitality, commercial and domestic settings.

KTC10P30/E27-S30 ()

Specification

Voltage	220-240Vac 50/60Hz
Current (mA)	45, 46
Rated Power (W)	10
CCT Words	Warm White
CCT (K)	3000K
Total Luminous Flux	720
Beam Angle(°)	30
Nominal Lifetime (h)	30000
SDCM (McAdam Ellipses) for CCT	2.2, 3.7
Power Factor	0.94, 0.96
Switch Cycles	50000
Warm-up Time 60% Φ (X.X S)	0.5
Warm-up Time 95% Φ (X.X S)	0.6
2) External LED control gear	No
Correction Factor	1
Lamp Cap	E27
LM at 6000h	0.85
LM at Nominal Lifetime	0.75
Mercury (X.X mg)	0
Prem Fail Rate at 1000h (%)	1
Rated Peak Candela (cd)	2200
Rated Useful Luminous Flux (Φ_{use})	590
Start Time (X.X S)	0.1

Light Source Specification

CRI	80, 82
-----	--------

Technical Drawings

