



## Aloba

### **Aloba Global Track Downlight, 24W, 38°, 3000K**

The Kosnic LED Track light is suitable for use with the Global 3 Circuit Track System. With a 350 degree rotation and 180 degree tilt, the Kosnic LED Track light is able to deliver a lot of light right where you need it. The LED Track light is particularly suitable for retail display, showrooms, galleries, and museums.

**KTDL24GL-S30 ()**

## Specification

|                                |                    |
|--------------------------------|--------------------|
| Voltage                        | 220-240Vac 50-60Hz |
| Current (mA)                   | 110                |
| Rated Power (W)                | 24                 |
| CCT Words                      | Warm White         |
| CCT (K)                        | 3000               |
| Total Luminous Flux (lm)       | 2000               |
| Beam Angle(°)                  | 38                 |
| Nominal Lifetime (h)           | 40000              |
| SDCM of CCT                    | <6                 |
| Power Factor                   | 0.95               |
| Ambient Temperature Range (°C) | -20 to 50          |
| Protection Rating              | Class I            |
| IP Rating                      | IP20               |

## Light Source Specification

|                                    |       |
|------------------------------------|-------|
| Dimmable (Y/N/Specific dimmer)     | No    |
| CCT                                | 3000K |
| CRI                                | 82    |
| Peak Luminous Intensity (DLS) (cd) | 3260  |
| Lumen Maintenance Factor (x.xx)    | 0.75  |

## Optional Gears and Accessories

|                  |                                     |
|------------------|-------------------------------------|
| Optional Gears 1 | Connection - Global 3 Circuit Track |
|------------------|-------------------------------------|

## Technical Drawings

