



Tatio

Tatio 9W Circular LED wall washer 15° 3000K

The Kosnic LED Wall Washer Downlight rotates through 350 degrees and has a 35 degree tilt. With a high CRI the downlight has many applications in retail display, showrooms, entertainment and hospitality. The downlight is available in colour temperatures of 3000K to replicate halogen lighting and 5000K day light. Manufactured from cast aluminium with a high-quality reflector the Kosnic Wall Washer Downlight delivers where a highly efficient, high quality lighting solution is required.

KWWDL09-B30 ()

Specification

Voltage	220-240Vac 50-60Hz
Current (mA)	69
Rated Power (W)	9
CCT Words	Warm White
CCT (K)	3000
Total Luminous Flux (lm)	1020
Beam angle(°)	15
Nominal Lifetime (h)	40000
SDCM of CCT	<6
Flicker %	5
Power Factor	0.57
Cut-out (mm)	82
Ambient Temperature Range (°C)	-20 to 50
Weight (kg)	0.6
Protection Rating	Class III Luminaire (Class II Driver)
IP Rating	IP20
Emergency Luminous Flux (lm)	350 (with CEW05LIL)
Driver Part Number	Tridonic LC 10W 250/350mA fixC SR SNC2
Driver Input Voltage	220-240 Vac 50-60 Hz
Driver Maximum Power (W)	10
Driver Output Voltage (Vdc)	23-40 Vdc
Driver Output Current (mA)	250
Driver Dimensions (L x W x D) (mm)	100 x 43 x 22.5 mm
Driver Power Factor	≥ 0.5
Driver Maximum Case Temperature (°C)	80 °C
Driver Inrush Current	15 A / 100 µs
Driver Protection	Class II / IP20

Light Source Specification

CCT	3000K
CRI	83

Technical Drawings

