



Tatio

Tatio 15W Chrome Circular LED wall washer 36° 5000K

The Kosnic LED Wall Washer Downlight rotates through 340 degrees and has a 63 degree tilt. With a high CRI the downlight has many applications in retail display, showrooms, entertainment and hospitality. The downlight is available in 16 degree and 36 degree beam angle options along with different colour temperatures of 3000K to replicate halogen lighting and cooler 5000K. Manufactured from cast aluminium with a high quality reflector the Kosnic Wall Washer Downlight delivers where a highly efficient, high quality lighting solution is required.

KWWDL15-S50-CHM ()

Specification

Voltage	220-240Vac 50-60Hz
Current (mA)	69
Rated Power (W)	15
CCT Words	Day Light
CCT (K)	5000
Total Luminous Flux (lm)	1250
Beam Angle(°)	36
Nominal Lifetime (h)	40000
SDCM of CCT	<6
Power Factor	0.95
Cut-Out (mm)	92
Ambient Temperature Range (°C)	-20 to 50
Protection Rating	Class III Luminaire (Class II Driver)
IP Rating	IP20
Emergency Luminous Flux (lm)	380 (with CEW05LIL)
Driver Part Number	PE096B1435
Driver Input Voltage	220-240 Vac 50-60 Hz
Driver Maximum Power (W)	15
Driver Output Voltage (Vdc)	25-42 Vdc
Driver Output Current (mA)	350
Driver Dimensions (L x W x D) (mm)	134 x 44 x 28 mm
Driver Power Factor	≥ 0.90
Driver Maximum Case Temperature (°C)	85 °C
Driver Inrush Current	<5 A at 300 µs
Driver Protection	Class II / IP20

Light Source Specification

CCT	5000K
CRI	82

Technical Drawings

