



Tatio

Tatio 24W Circular LED wall washer 38° 5000K

The Kosnic LED Wall Washer Downlight rotates through 340 degrees and has a 45 degree tilt. With a high CRI the downlight has many applications in retail display, showrooms, entertainment and hospitality. The downlight is available in 15 degree and 38 degree beam angle options along with different colour temperatures of 3000K to replicate halogen lighting and cooler 5000K. Manufactured from cast aluminium with a high quality reflector the Kosnic Wall Washer Downlight delivers where a highly efficient, high quality lighting solution is required.

KWWDL24-S50 ()

Specification

Voltage	220-240Vac 50-60Hz
Current (mA)	110
Rated Power (W)	24
CCT Words	Day Light
CCT (K)	5000
Total Luminous Flux (lm)	2000
Beam angle(°)	38
Nominal Lifetime (h)	40000
SDCM of CCT	<6
Power Factor	0.95
Cut-out (mm)	145
Ambient Temperature Range (°C)	-20 to 50
Protection Rating	Class III Luminaire (Class II Driver)
IP Rating	IP20
Emergency Luminous Flux (lm)	220 (with KTC27EME-DWL)
Driver Part Number	CYC026SNL058N
Driver Input Voltage	180-264Vac 50-60Hz
Driver Maximum Power (W)	26
Driver Output Voltage (Vdc)	26~46Vdc
Driver Output Current (mA)	580
Driver Dimensions (L x W x D) (mm)	154 x 47 x 34
Driver Power Factor	0.96
Driver Maximum Case Temperature (°C)	75
Driver Inrush Current	1 at 400µs
Driver Protection	Class II / IP20

Light Source Specification

Light Source Cap Type (or other interface)	Connection - Driver wiring leads
Dimmable (Y/N/Specific dimmer)	No

CCT	5000K
CRI	82

Technical Drawings

