



Tatio-R

Tatio-R Rectangular LED wall washer

The Kosnic LED Wall Washer Downlight is recessed into the ceiling and tilts through 45 degrees. With a high CRI the downlight has many applications in retail display, showrooms, entertainment and hospitality. The downlight has a 110 degree beam angle and is available with different colour temperatures from 3000K to replicate halogen lighting to cooler 6000K. Manufactured from cast aluminium with a high quality reflector the Kosnic Wall Washer Downlight delivers where a highly efficient, high quality lighting solution is required.

KWWDL25Q-W60 ()

Specification

Voltage	220-240 Vac 50-60 Hz
Current (mA)	114
Rated Power (W)	25
CCT Words	Day Light
CCT (K)	5000
Total Luminous Flux (lm)	2150
Beam Angle(°)	110
L70B50 Lifetime (h)	40000
SDCM of CCT	<6
Power Factor	0.95
Cut-Out (mm)	220 x 130
Ambient Temperature Range (°C)	-20 to 40
Protection Rating	Class III Luminaire, Class II Driver
IP Rating	IP20
Emergency Luminous Flux (lm)	160 (with KTC27EME-DWL)
Driver Part Number	CYC025SNL070N
Driver Input Voltage	180-264Vac 50-60Hz
Driver Maximum Power (W)	25
Driver Output Current (mA)	700
Driver Dimensions (L x W x D) (mm)	154 x 47 x 34
Driver Ripple Current (%)	<10
Driver Maximum Case Temperature (°C)	75
Output Voltage (Vdc)	26-36Vdc

Light Source Specification

Light Source Cap Type (or other interface)	Connection - Driver wiring leads
Dimmable (Y/N/Specific dimmer)	No
CRI	82

Technical Drawings