



Tatio

Tatio 34W Circular LED wall washer 15° 3000K

The Kosnic LED Wall Washer Downlight rotates through 350 degrees and has a 60 degree tilt. With a high CRI the downlight has many applications in retail display, showrooms, entertainment and hospitality. The downlight is available in 15 degree and 40 degree beam angle options along with different colour temperatures of 3000K to replicate halogen lighting and cooler 5000K. Manufactured from cast aluminium with a high quality reflector the Kosnic Wall Washer Downlight delivers where a highly efficient, high quality lighting solution is required.

KWWDL34-B30 ()

Specification

Voltage	220-240Vac 50-60Hz
Current (mA)	155
Rated Power (W)	34
CCT Words	Warm White
CCT (K)	3000
Total Luminous Flux (lm)	2800
Beam angle(°)	15
Nominal Lifetime (h)	40000
SDCM of CCT	<6
Power Factor	0.95
Cut-out (mm)	170
Ambient Temperature Range (°C)	-20 to 50
Protection Rating	Class III Luminaire (Class II Driver)
IP Rating	IP20
Emergency Luminous Flux (lm)	220 (with KTC27EME-DWL)
Driver Part Number	CYC036SNL080N
Driver Input Voltage	180-264 Vac
Driver Maximum Power (W)	36
Driver Output Voltage (Vdc)	30~46 Vdc
Driver Output Current (mA)	800
Driver Dimensions (L x W x D) (mm)	154 x 47 x 34
Driver Power Factor	≥0.96
Driver Maximum Case Temperature (°C)	75
Driver Inrush Current	1A at 400µs
Driver Protection	Class II / IP20

Light Source Specification

Light Source Cap Type (or other interface)	Connection - Driver wiring leads
Dimmable (Y/N/Specific dimmer)	No

CCT	3000K
CRI	82

Technical Drawings

