



Reon PAR

11W LED E27 Dimmable lamp, PAR38 Shape 60Deg

The Reon LED PAR20 lamps offer huge energy savings over halogen lamps without compromising on brightness. The lamps can quickly replace halogen products in accent and general lighting applications, and once in place rapid payback is achieved.

P3811DIM/E27-S27 ()

Specification

Voltage	220-240Vac 50/60Hz
Current (mA)	80
Rated Power (W)	11
CCT Words	Warm White
CCT (K)	2700
Total Luminous Flux (lm)	1000
L70B50 Lifetime (h)	15000
Blue Light Hazard	RG1
Glow wire temperature(°C)	650
Power Factor	0.6
Ambient Temperature Range (°C)	-20 to 40
Weight (kg)	0.202

Light Source Specification

Lighting Technology Used	LED
Directional / Non Directional (DLS/NDLS)	DLS
Light Source Cap Type (or other interface)	E27
Mains / Non-Mains (MLS/NMLS)	MLS
Connected Light source (Y/N)	N
Colour Tunable Light Source (Y/N)	N
High Luminance Light Source (Y/N)	N
Anti-Glare Shield (Y/N)	N
Dimmable (Y/N/Specific dimmer)	Y
Energy Consumption in on-mode (kWh/1000H)	11
Energy Efficiency Class	F
Useful Luminous Flux (lm)	880
Beam Angle correspondence (in 360°/120°/90°)	in 90°
CCT	2700
On-Mode Power (Pon) (W)	11

Standby Power (Psb) (W)	0
Networked Standby Power (Pnet) (W)	N/A
CRI	82
CRI (min)	80
CRI (max)	84
Height (mm)	139
Width (mm)	120
Depth (mm)	120
Claim of Equivalent Power? (Y/N)	Y
Equivalent Power (W)	103
Chromaticity Co-Ordinates (X)	0.462
Chromaticity Co-Ordinates (Y)	0.415
Peak Luminous Intensity (DLS) (cd)	3400
Beam Angle (DLS)	30
Beam Angle (min)(DLS)	28
Beam Angle (max) (DLS)	32
Survival Factor (x.xx)	0.9
Lumen Maintenance Factor (x.xx)	0.93
Displacement Factor	0.8
Colour Consistency in Mcadam Ellipses (Mains LED/OLED)	6
LED light source replaces fluorescent without integrated ballast of particular wattage (Mains LED/OLED) (Y/N)	N
Replacement W Claim (Mains LED/OLED) (W)	N/A
Flicker metric (pst LM) (x,x)	0.1
Stroboscopic effect metric (SVM) (x,x)	0.1

Technical Drawings

